



TC-720+

Urine Analyzer

For over 30 years, Teco Diagnostics has been an industry leader in the manufacturing of in-vitro clinical diagnostic tests and instruments. From powder to liquid clinical chemistry, we have high quality solutions for your diagnostic needs. Based in Anaheim, CA, our manufacturing facility is FDA regulated, and thus all phases of our production processes are based on strict Current Good Manufacturing Practices (cGMP) regulations which safeguard the excellent quality of all our products.



FDA Registered and cGMP
Compliant Manufacturer
ISO 13485:2016 Certified
SA8000 Certified I CE



TC-720+

Urine Analyzer



Test Principle

Reflectance photometry

Parameters Detected

Urine Occult Blood (BLD), Leucocytes (LEU), Specific Gravity (SG), (pH), Protein (PRO), Urobilinogen (URO), Bilirubin (BIL), Ketones (KET), Glucose (GLU), Nitrite (NIT), Ascorbic Acid (VC).

Microalbumin/Creatinine (ACR) reportable.

Features

- High throughput up to 514 tests/hour
- Automatic correction on the influence of non-specificity, pH, SG and color on the test results
- LCD touch screen with user-friendly interface
- Automatic collection of used test strips
- Built-in low noise thermal printer, External printer connectable
- Automatic results saving and uploading function available
- With power-on self-checking and automatic fault reporting system. Automatic error warning system. LCD Touch Screen
- NMPA approved original quality control materials available

Specifications

Throughput	≤514 tests/hour
Test Strips	URS-2MP, URS-10 and URS-11 (optional)
Repeatability	Test result CV ≤1%
Accuracy	The difference between test results and target values is no more than one level; no false negative result when tested with positive reference solution and no false positive result when tested with negative reference solution
Stability	Test result CV ≤1% with power on of 8 hours
Printing	built-in thermal printers, external printer (optional)
Storage	≥100000 test results
Relative Humidity	30% - 80%
Working Temperature	5-40°C (41- 104°F)
Working Voltage	AC 100-240V, 50Hz
Power	100-240V-50/60Hz, 250VA
Dimensions	380*320*190mm
Weight	4.5kg